Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-VALVOLINE
Valvoline LLC	
3499 Blazer Parkway	Regulatory Information Number
Lexington, KY 40509	1-800-TEAMVAL
United States of America (USA)	
1-800-TEAMVAL	Product Information
	1-800-TEAMVAL
	1-800-TEAMVAL
	1 222 1 2 1 1 1 1 1 2

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	Not a hazardous substance or mixture.	5.2547
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	1.1945
Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts	113706-15-3	Skin Irrit. 2; H315 Eye Dam. 1; H318	1.036

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

Sulphur oxides hydrogen sulfide mercaptans zinc oxide

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components with workplace control parameters				
Components	CAS-No.	Value type	Control	Basis
		(Form of	parameters /	
		exposure)	Permissible	
			concentration	
HYDROTREATED LIGHT	64742-55-8	TWA	5 mg/m3	OSHA Z-1
PARAFFINIC DISTILLATE			Mist	
		TWA	5 mg/m3	ACGIH
			Inhalable fraction	
		TWA	5 mg/m3	OSHA P0
			Mist	
		TWA	5 mg/m3	NIOSH REL
			Mist	
		ST	10 mg/m3	NIOSH REL
			Mist	
		PEL	5 mg/m3	CAL PEL
			particulate	

Hazardous components without workplace control parameters

Components	CAS-No.	
------------	---------	--

Engineering measures : General room ventilation should be adequate for normal

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment

supplier).

Wear as appropriate:

Safety shoes

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

Colour : amber

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : > 424.9 °F / 218.3 °C

Flash point : > 199 °C

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)

Calculated Explosive Limit

Lower explosion limit : 1 %(V)

Calculated Explosive Limit : 0.0133333 hPa (21.11 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.880 g/cm3 (15.56 °C)

Solubility(ies)

Vapour pressure

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 115 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Acids

Strong oxidizing agents

water

Hazardous decomposition

products

carbon dioxide and carbon monoxide

Hydrocarbons hydrogen sulfide Nitrogen oxides (NOx)

Sulphur oxides zinc oxide mercaptans

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Skin contact
Eye Contact

Lye Conta

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): 2,900 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Skin corrosion/irritation

Not classified based on available information.

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Test Type: Buehler Test Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Genotoxicity in vitro : Remarks: In vitro tests showed mutagenic effects which were

not observed with in vivo test.

Genotoxicity in vivo : Test Type: chromosome aberration assay

Test species: Mouse

Cell type: peripheral blood cells

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Effects on fertility : Species: Rat

Application Route: Oral Dose: 100 mg/kg bw/day

Symptoms: No effects on reproduction parameters

Effects on foetal : Species: Rat

development Application Route: Oral

Developmental Toxicity: No observed adverse effect level F1:

100 mg/kg body weight

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from

similar substances.

Persistence and degradability

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

Remarks: Information given is based on data obtained from

similar substances.

No data available

Bioaccumulative potential

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Bioaccumulation : Bioconcentration factor (BCF): 3

Remarks: Information given is based on data obtained from

similar substances.

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

REGULATION					
ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

	0.0. 00.	NO 1D
I		Not dangerous goods
ſ		

CFR_RAIL_C

		Page: 10
V	<u>alvoline.</u>	
SAFETY DATA SHE	ET	Revision Date: 09/23/2016
		Print Date: 9/27/2016
		SDS Number: R0306034
NAPA® Heavy Duty Diesel S	AE 15W-40 Engine Oil	Version: 1.4
869974		
Not dange	rous goods	
140t dange	90005	
I.S. DOT - INLAND WATERV	VAYS	
	rous goods	
DG_ROAD_C		
	rous goods	
-		
DG_RAIL_C		
	rous goods	
DG_INWT_C		
Not dange	rous goods	
NTERNATIONAL MARITIME	DANGEROUS GOODS	
Not dange		
-		
NTERNATIONAL AIR TRANS	SPORT ASSOCIATION - CARGO	
Not dange		
NTERNATIONAL AIR TRANS	SPORT ASSOCIATION - PASSENGER	8
	rous goods	•
-		
/IX_DG		
	rous goods	
Ŭ		
ORM = ORM-D, CBL = COM	BUSTIBLE LIQUID	
Marine pollutant	l no	
ivianne ponutant	no	
	ns (if indicated above) may not reflect q	
exceptions that can be applied	ed. Consult shipping documents for de-	scriptions that are specific to the

shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards

SARA 313

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and 113706-15-3 1.03 %

isooctyl) esters, zinc salts

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 09/23/2016



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 9/27/2016
	SDS Number: R0306034
NAPA® Heavy Duty Diesel SAE 15W-40 Engine Oil	Version: 1.4
869974	

TWA: Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System